

# Laykold®

## White Line Paint

ADVANCED POLYMER TECHNOLOGY

109 CONICA LANE, PO BOX 160

HARMONY, PA 16037

TEL (412) 452-1330 FAX (412) 452-1703

Effective April 1, 1998 - New Area Code (724)

### PRODUCT DESCRIPTION

LAYKOLD White Line Paint is a water-based, 100% acrylic emulsion line marking paint. White Line Paint contains no solvents or oils that tend to attack the underlying surface causing cracking or crazing.

Line Paint is available in both textured (with silica sand) or regular (without silica sand) and in 1 gallon or 5 gallon units. LAYKOLD White Line Paint contains NO asbestos, lead, or mercury.

LAYKOLD White Line Paint is used for marking lines over color coating materials on tennis courts, basketball courts, and other recreational surfaces. White Line Paint may also be used directly over asphalt surfaces.

### SURFACE PREPARATION

Existing surface shall be clean, free from all dirt, dust and foreign debris, and shall be dry. New asphalt and concrete should be allowed a 30 day curing period before applying any coatings.

### INSTALLATION

Wait approximately 24 hours after applying color coatings, before applying White Line Paint. For indoor installations, wait until color coating materials are thoroughly cured.

Mix LAYKOLD White Line Paint completely before applying. Do NOT add water. Tape and measure lines in accordance with the United States Tennis Court & Track Builders Association specifications.

Brush or roll line paint in 1-2 coats depending on specification. To improve crispness of the finished line, prime the tape, prior to application of the line paint, with the same finish color coat material in which the surface has been coated.

### COVERAGE

LAYKOLD White Line Paint coverage is approximately .75-1 gallon of line paint per standard size tennis court.

### LIMITATIONS

- Do not apply when temperatures are below 50°F (10°C) or when rain is imminent.
- Do not allow to freeze.
- Do not dilute.
- Drying time of 2-4 hours depending on weather conditions.

### WARRANTY

APT warrants its products to be free of manufacturing defects and to meet published physical properties when applied, cured, and tested in accordance with the ASTM and APT standards. This warranty is in lieu of all warranties expressed or implied including any warranty of merchantability or fitness for a particular purpose in connection with this product. Neither seller nor supplier shall be liable for any loss or damage either direct, incidental or consequential regardless of legal theory asserted, including negligence, merchantability and/or strict liability. Seller's and supplier's obligation shall be to replace such quantity of product proven to be defective. Before using, user shall determine suitability of product for the intended use and user assumes all risk in connection therewith.