



## **SPEED-FLEX L400**

**DESCRIPTION:** SPEED-FLEX is a carboxylated styrene butadiene (SBR) latex running track surface consisting of multiple layers of rubber particles broadcast over a pervious or impervious base. Each layer of rubber shall be bound with latex binder. The Result is an economical, seamless, self sealing all weather surface.

### **PHYSICAL PROPERTIES OF FINISHED SURFACE:**

**Thickness:** 3/8"  
**Color:** Black

**Minimum Total Rubber:** 10 lbs. / sq. yd.  
**Minimum Total Binder:** .965 gal. / sq. yd.

**Cure Time:** Approximately 4 hours (each layer) in warm, dry, ambient temperatures (installation is not recommended after October 1<sup>st</sup> in northern latitudes.)

### **CLEAN UP:**

The contractor shall remove all debris, bags and pallets associated with the installation. Normal installation procedures result in minor overspray along track edges. Removal of this overspray shall not be required unless specified.

### **EVENT MARKINGS:**

The measurements and markings of lines and events shall be performed in accordance with the requirements of the local governing body. The paint used shall be latex paint as recommended by the manufacturer.

SPEED FLEX L400 is a product of :

**Reece Seal Coating, Inc.**

1205 W. Troy

Indianapolis, IN 46225

Tel (800) 783-1406

Fax (317) 784-1410

[www.reeceinc.com](http://www.reeceinc.com)